USSN: 10/602,900

IN THE CLAIMS:

Please revise claim 55 and add new claims 75-84 as follows:

and

55. (Amended) A method for contacting at least two chemical species, comprising:

immobilizing an immobilized chemical species on a fiber; placing said fiber on a support having across a channel formed in said support;

disposing a mobile chemical species into said channel such that said immobilized mobile chemical species contacts said immobilized chemical species on said fiber.

- 75. (New) The method of claim 55 wherein said immobilizing step includes immobilizing a different polynucleotide on each of a plurality of said fibers.
- 76. (New) The method of claim 55 further comprising the step of moving said second chemical along said channel.
- 77. (New) The method of claim 76 wherein said moving step includes the step of applying electro-osmotic force to said channel.
- 78. (New) A method for analyzing the contact between at least two chemical species, comprising:

immobilizing an immobilized chemical species on at least a first one of a plurality of optical fibers;

placing said plurality of fibers on a support having a plurality of channels;

disposing a mobile chemical species into at least a first one of said plurality of channels such that said mobile chemical species contacts at least said first one of a plurality of optical fibers;

directing light to an end of said at least a first one of a plurality of optical fibers; and viewing the light emitted from said at least a first one of a plurality of optical fibers.

- 79. (New) The method of claim 78 wherein said directing step is accomplished by directing said light through a focusing lens.
- 80. (New) A method for detecting the binding of two chemical species, comprising the steps of:

1-PA/3516164.1 3

USSN: 10/602,900

directing light at a fiber positioned in a support for holding a plurality of fibers substantially parallel to each other and having a plurality of channels aligned substantially parallel to each other for receiving one or more mobile chemical species, such that each fiber is in fluid communication with the one or more mobile chemical species, where the fiber has an immobilized chemical species thereon; and

detecting excitation light emitted from binding occurring between said immobilized chemical species and at least one of said one or more mobile chemical species.

81. (New) The method of claim 80, wherein said detecting step comprises the steps of:

collecting said excitation light to produce collected excitation light; and converting said collected excitation light into an electrical signal that is proportional to said collected excitation light.

- 82. (New) The method of claim 81, wherein said detecting step comprises the step of detecting light emitted from said labeled chemical species at a plurality of predetermined locations along said fiber.
- 83. (New) The method of claim 81, further comprising the step of gradually changing the temperature of the fiber over a predetermined range of temperature such that the temperature of said fiber will pass through an optimum temperature for binding of at least one of said one or more mobile chemical species and said immobilized chemical species.
- 84. (New) A method according to claim 81, further comprising the step of verifying the chemical composition of said immobilized chemical species or said one or more mobile chemical species.